



4 PoE PORTS

Plus one uplink

100Mbps

Data transfer rate

65W MAX POWER

15.4W per port

IEEE 802.3af

Standard

POWER PROTECTION

On low powered devices

UNMANAGED

Ports automatically detect devices

Standard

IEEE 802.3af
IEEE 802.3 10BASE-T
IEEE 802.3u 100BASE-TX
IEEE 802.3x Flow Control

Number of PoE Ports

4 PoE + 1 Uplink

MAC Address Table

2K

Buffer Memory

512KB

Transmission Method

Store and Forward

Filtering/Forwarding Rates

100Mbps Port - 148,800pps
10Mbps Port - 14,880pps

Transmission Media

100BaseTx Cat5 UTP/STP
10BaseT Cat3, 4, 5 UTP/STP

LED Indicators

Per Port: Link/Act w/ 10/100Mbps, On/Off
Per Unit: Power

PoE Output Pin Configuration

Mode-A 1/2 (+), 3/6 (-)

Power Input

100-240VAC, 50-60Hz

Power Output

54VDC 1.25A

Power Consumption

65W Max, 15.4W per Port

Dimensions

7.31" x 4.88" x 1.69"

Weight

0.8 lbs

Operating Temperature

32°F to 131 °F

Storage Temperature

-4°F to 194°F

Humidity

10 to 90% RH (Non-condensing)

Certifications

FCC Class B, CE